

# Packsaddle Series



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	30W, 50W, 60W, 90W, 100W, 120W, 150W, 180W, 200W, 240W
Efficacy	160lm/W
Correlated Colour Index (CRI)	CRI: >70, CRI: >80
IP Rating	IP65
IK Rating	IK10

ATTRIBUTE	VALUES
Voltage	AC100-277V
Size - Length	Length: 718mmL, Length: 280mmL, Length: 948mmL, Length: 486mmL, Length: 1178mmL
Size - Width	Width: 137mmW
Size - Height	Height: 102mmH
Beam Angle	Beam Angle: 90°, Beam Angle: 120°, Beam Angle: 30° x 70°, Beam Angle: 40° x 120°, Beam Angle: 50° x 90°, Beam Angle: Asymmetrical - 40°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, ZigBee Controls

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 718mmL, Length: 280mmL, Length: 948mmL, Length: 486mmL, Length: 1178mmL
Size - Height	Height: 102mmH
Beam Angle	Beam Angle: 90°, Beam Angle: 120°, Beam Angle: 30° x 70°, Beam Angle: 40° x 120°, Beam Angle: 50° x 90°, Beam Angle: Asymmetrical - 40°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, ZigBee Controls

## Certification and Compliance

