

## Edith Series - 88 - SMD



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, TBC, 15W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	66, TBC
IK Rating	05
Voltage	AC220-240V, 50/60Hz, DC 24V
Light Source & Brand	LED: CREE SMD
Driver	Driver: Meanwell, Driver: Done
Size - Length	Length: 88mmL
Size - Width	Width: 88mmW
Size - Height	Height: 156mmH
Weight	Weight: 1.8kg
Vertical Rotation	Vertical Rotation: 180°
Beam Angle	TBC, Beam Angle: 3°, Beam Angle: 6°, Beam Angle: 10°, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 6° x 40°, Beam Angle: 10° x 20°, Beam Angle: 10° x 30°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics-Glare control	Optics Material: 4mm Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Mounting Options	Surface Mounted, TBC
Lens Options	TBC, Honeycomb Louve
Accessories	Cubic Hood, 25° Cubic Hood
Lifetime	Reported L80 @ 85° >90,700 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 88mmL
Size - Height	Height: 156mmH
Beam Angle	TBC, Beam Angle: 3°, Beam Angle: 6°, Beam Angle: 10°, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 6° x 40°, Beam Angle: 10° x 20°, Beam Angle: 10° x 30°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Cubic Hood, 25° Cubic Hood

## Certification and Compliance

