

## Abbotsford Series - 600



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	100W
Efficacy	160lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <5
IP Rating	IP65

ATTRIBUTE	VALUES
IK Rating	IK10
Voltage	AC100-277V
Light Source & Brand	LED: SMD
Driver	Driver: Meanwell
Size - Length	Length: 623mmL
Size - Width	Width: 138mmW
Size - Height	Height: 73mmH
Mounting Options	Surface Mounted, Suspended
Beam Angle	Beam Angle: 60°, Beam Angle: 90°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 3CCT: 3000K+4000K+5000K
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls, Honeycomb Optics
Weight	Weight: 5.9kg
Material of Housing	Housing Material: Die-Casting Aluminum

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 623mmL
Size - Height	Height: 73mmH
Beam Angle	Beam Angle: 60°, Beam Angle: 90°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls, Honeycomb Optics
Material of Housing	Housing Material: Die-Casting Aluminum

## Certification and Compliance

