

Gadgarra Series - 600

[AES-25-HB560-600]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W
Efficacy	140lm/W, 160lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	65, TBC
IK Rating	10
Voltage	AC100-277V
Light Source & Brand	LED: SMD
Driver	Driver: Meanwell

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Size - Length	Length: 623mmL
Size - Width	Width: 138mmW
Size - Height	Height: 73mmH
Mounting Options	Surface Mounted, Suspended, TBC
Beam Angle	TBC, Beam Angle: 60° x 90°, Beam Angle: 90° x 110°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 3CCT: 3000K+4000K+5000K
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls, Honeycomb Optics
Weight	Weight: 5.9kg
Material of Housing	Housing Material: Die-Casting Aluminum

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 623mmL
Size - Height	Height: 73mmH
Beam Angle	TBC, Beam Angle: 60° x 90°, Beam Angle: 90° x 110°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls, Honeycomb Optics
Material of Housing	Housing Material: Die-Casting Aluminum

Certification and Compliance

