

# Troffer Series - 1230

[AES-27-GL002-30120]



## Technical Specifications

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Wattages                            | TBC, 32W   |
| Efficacy                            | 115lm/W  |
| Correlated Colour Index (CRI)       | >80, TBC   |
| MacAdam Ellipse (SDCM)              | <6   |
| IP Rating                           | 20, TBC  |
| IK Rating                           | 06   |
| Voltage                             | AC220-240V   |
| Light Source & Brand                | LED: SMD 2835  |
| Driver                              | Driver: Built-out  |
| Size - Length                       | Length: 1195mmL  |
| Size - Width                        | Width: 295mmW  |
| Size - Height                       | Height: 54mmH  |
| Weight                              | Weight: 2.53kg   |
| Beam Angle                          | TBC, Beam Angle: 130°  |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable             |
| Material of Housing                 | Housing Material: SPCC   |
| Material of Optics- Glare control   | Optics Material: PMMA + PC   |
| Operating Temperature               | Operating Temperature: -10°C to 45°C   |
| Trim / Outer Colour                 | Trim/Outer: White  |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 3CCT: 3000K+4000K+5000K |
| Mounting Options                    | TBC, Recessed  |
| Lamp Life                           | Lamp Life: 50,000 hrs  |

## Product Options

| ATTRIBUTE     | VALUES                |
|---------------|-----------------------|
| Size - Length | Length: 1195mmL       |
| Size - Height | Height: 54mmH         |
| Beam Angle    | TBC, Beam Angle: 130° |

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: SPCC   |
| Operating Temperature | Operating Temperature: -10°C to 45°C                             |

## Certification and Compliance

