

Underwood Series - 250

[AES-36-2250RIG-A]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 14 x 2W (28W), 16 x 2W (32W), 18 x 2W (36W)
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	67, TBC
IK Rating	10
Voltage	AC220-240V, 50/60Hz, DC 24V
Light Source & Brand	LED: CREE
Size - Diameter	Diameter: 250mmØ
Size - Height	Height: 190mmH
Cut Out Size - Diameter	Cut Out: 223mmØ
Tilt	Tilt: 25°
Beam Angle	TBC, Beam Angle: 8°, Beam Angle: 15°, Beam Angle: 25°, Beam Angle: 40°, Beam Angle: 60°, Beam Angle: 10° x 45°, Beam Angle: 20° x 65°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics- Glare control	Optic Material: Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K
Accessories	ABS Mounting Sleeve, 316SUS Front Cover
Mounting Options	TBC, Recessed
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 250mmØ
Size - Height	Height: 190mmH
Beam Angle	TBC, Beam Angle: 8°, Beam Angle: 15°, Beam Angle: 25°, Beam Angle: 40°, Beam Angle: 60°, Beam Angle: 10° x 45°, Beam Angle: 20° x 65°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	ABS Mounting Sleeve, 316SUS Front Cover

Certification and Compliance

