

Queenwood Series - 180

[AES-36-2180RIG-B]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | TBC, 14W, 16W, 18W, 20W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| IP Rating | 67, TBC |
| IK Rating | 10 |
| Voltage | AC220-240V, 50/60Hz, DC 24V |
| Light Source & Brand | LED: Cree COB |
| Size - Diameter | Diameter: 180mmØ |
| Size - Height | Height: 162mmH |
| Cut Out Size - Diameter | Cut Out: 165mmØ |
| Tilt | Tilt: 25° |
| Beam Angle | TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 30° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum |
| Material of Optics- Glare control | Optic Material: Tempered Glass |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K |
| Accessories | ABS Mounting Sleeve, 316SUS Front Cover |
| Mounting Options | TBC, Recessed |
| Lamp Life | Lamp Life: L80 B10 @ 4K, CRI80 |

Product Options

| ATTRIBUTE | VALUES |
|-----------------|---|
| Size - Diameter | Diameter: 180mmØ |
| Size - Height | Height: 162mmH |
| Beam Angle | TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 30° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable |

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Accessories | ABS Mounting Sleeve, 316SUS Front Cover |

Certification and Compliance

