

## Gardenvale Series - 210



### Technical Specifications

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| Wattages                            | TBC, 21W, 23W, 25W  |
| Correlated Colour Index (CRI)       | >80, >90, TBC   |
| IP Rating                           | 67, TBC   |
| IK Rating                           | 10  |
| Voltage                             | AC220-240V, 50/60Hz, DC 24V   |
| Light Source & Brand                | LED: Cree COB   |
| Size - Diameter                     | Diameter: 210mmØ  |
| Size - Height                       | Height: 175mmH  |
| Cut Out Size - Diameter             | Cut Out: 183mmØ   |
| Tilt                                | Tilt: 25°   |
| Beam Angle                          | TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 30° |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable  |
| Material of Housing                 | Housing Material: Die-Cast ADC12 Aluminum   |
| Material of Optics- Glare control   | Optic Material: Tempered Glass  |
| Operating Temperature               | Operating Temperature: -20°C to +40°C   |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K  |
| Accessories                         | 316SUS Front Cover  |
| Mounting Options                    | TBC, Recessed   |
| Lamp Life                           | Lamp Life: L80 B10 @ 4K, CRI80  |

## Product Options

| ATTRIBUTE           | VALUES  |
|---------------------|---|
| Size - Diameter     | Diameter: 210mmØ  |
| Size - Height       | Height: 175mmH  |
| Beam Angle          | TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 30° |
| Dimming Options     | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable  |
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum   |

| ATTRIBUTE             | VALUES                                |
|-----------------------|---------------------------------------|
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Accessories           | 316SUS Front Cover                    |

## Certification and Compliance

