

Jackadgery Series - 100W

[AES-25-HB430-100]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W
Efficacy	150lm/W, 190lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	65, TBC
IK Rating	10
Voltage	AC100-277V
Light Source & Brand	LED: SMD
Driver	Driver: Phillips, Driver: Meanwell, Driver: SOSEN
Size - Diameter	Diameter: 300mmØ
Size - Height	Height: 155mmH

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 110°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls
Material of Housing	Housing Material: Die-Casting Aluminum
Lens Options	TBC, Glass Cover
Weight	Weight: 4.3kg
Mounting Options	TBC, Bracket Mounted, Ceiling Mounted, Hook Mounted, Loop Hanging

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 300mmØ
Size - Height	Height: 155mmH
Beam Angle	TBC, Beam Angle: 110°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls
Material of Housing	Housing Material: Die-Casting Aluminum

Certification and Compliance

