

# Hammondville Series - 160

[AES-36-7160RC-SMD]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 2 x 2W (4W), 4 x 2W (8W), 6 x 2W (12)
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	67, TBC
IK Rating	10
Voltage	AC220-240V, 50/60Hz, DC 24V

ATTRIBUTE	VALUES
Light Source & Brand	LED: Cree COB
Size - Diameter	Diameter: 160mmØ
Size - Height	Height: 149mmH
Cut Out Size - Diameter	Cut Out: 143mmØ
Tilt	Tilt: 25°
Beam Angle	TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 30°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics- Glare control	Optic Material: Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K
Accessories	316SUS Front Cover
Mounting Options	TBC, Recessed
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 160mmØ
Size - Height	Height: 149mmH
Beam Angle	TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 30°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	316SUS Front Cover

## Certification and Compliance

