

# Calala Series - 100 St Aloysius



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, TBC, 30W, 33W, 35W
Efficacy	120lm/W
Correlated Colour Index (CRI)	>80, >92, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB
Driver	Driver: Built In
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 220mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Gold
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT
Material of Housing	Housing Material: Aluminium + Transparent Tempered Glass

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 220mmH
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium + Transparent Tempered Glass

## Certification and Compliance

