

# Ottoway Series - 70W

[AES-37-AL140-70W]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 55W, 60W, 65W, 70W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>70, >80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	66, TBC
IK Rating	08
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: Lumileds 5050
Driver	Invertronics EUM
Size - Length	Length: 328mmL
Size - Width	Width: 240mmW

ATTRIBUTE	VALUES
Size - Height	Height: 99mmH
Weight	Weight: 3.8kg
Beam Angle	TBC, Type IV - T4, Type V - VSM, Type II-III - T4, Type II-III - SCL, Type II-III - SCL-PC
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Lens Options	TBC, Toughened Glass
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Mounting Options	TBC, Pole Mounted, Wall Mounted
Accessories	Junction Box for Wall Mounting, 60mmø square tube bracket for pole wall mounting, 40mmø round pipe bracket for pole mounting
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 328mmL
Size - Height	Height: 99mmH
Beam Angle	TBC, Type IV - T4, Type V - VSM, Type II-III - T4, Type II-III - SCL, Type II-III - SCL-PC
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C
Accessories	Junction Box for Wall Mounting, 60mmø square tube bracket for pole wall mounting, 40mmø round pipe bracket for pole mounting

## Certification and Compliance

