

# Pacific Series - Recessed - 60W

[AES-03-GS01-G3-R-60W]



## Technical Specifications

| ATTRIBUTE | VALUES |
|-----------|--------|
|-----------|--------|

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| Wattages                            | TBC, 60W  |
| Efficacy                            | 140lm/W   |
| Correlated Colour Index (CRI)       | >80, TBC  |
| MacAdam Ellipse (SDCM)              | <6  |
| IP Rating                           | 65, TBC   |
| IK Rating                           | 08  |
| Voltage                             | AC100-277V, 50/60Hz   |
| Light Source & Brand                | LED: SMD 3030   |
| Driver                              | Driver: SOSEN   |
| Size - Length                       | Length: 464mmL  |
| Size - Width                        | Width: 430mmW   |
| Size - Height                       | Height: 112mmH  |
| Weight                              | Weight: 7.7kg   |
| Beam Angle                          | TBC, Beam Angle: 120°   |
| Dimming Options                     | Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable  |
| Material of Housing                 | Housing Material: Die-Cast ADC12 Aluminum Alloy   |
| Material of Optics- Glare control   | Optics Material: Polycarbonate Lens   |
| Corrosion Resistance                | Corrosion Resistance: C5  |
| Operating Temperature               | Operating Temperature: -40°C to+50°C  |
| Trim / Outer Colour                 | Trim/Outer: White   |
| Reflector / Internal Colour         | Reflector/Internal: White   |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5700K  |
| Mounting Options                    | TBC, Recessed   |
| Lifetime                            | Reported L80 @ 85° >70,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

## Product Options

| ATTRIBUTE     | VALUES         |
|---------------|----------------|
| Size - Length | Length: 464mmL |

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Size - Height         | Height: 112mmH                                   |
| Beam Angle            | TBC, Beam Angle: 120°                            |
| Dimming Options       | Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: Die-Cast ADC12 Aluminum Alloy  |
| Operating Temperature | Operating Temperature: -40°C to+50°C             |

## Certification and Compliance

