

Tahara Series - 1200



Technical Specifications

ATTRIBUTE	VALUES
Wattages	20W, 22W, 24W, 26W, 28W, 30W, 32W, 34W, 36W, 38W, 40W
Efficacy	120lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <5
IP Rating	IP67
IK Rating	IK08
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Driver	Driver: MFU28D-40P
Size - Length	Length: 1200mmL
Size - Width	Width: 99.76mmW
Size - Height	Height: 75.77mmH
Weight	Weight: 1.86kg
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -20°C to +50°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: White
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	Ceiling Mounted
Accessories	Emergency, Motion Sensor
Lens Options	120D
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1200mmL

ATTRIBUTE	VALUES
Size - Height	Height: 75.77mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +50°C
Accessories	Emergency, Motion Sensor

Certification and Compliance

