

# Abbeyard Series

[AES-01-CP02]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 25W, 40W, 60W, 80W, 100W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	65, TBC

ATTRIBUTE	VALUES
IK Rating	08
Voltage	AC100-277V
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 80°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Accessories	Microwave Sensor, PIR Sensor, CCT Selectable Switch, 4 Power Selectable Switch
Operating Temperature	Operating Temperature: -30°C to +50°C

## Product Options

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 80°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, CCT Selectable Switch, 4 Power Selectable Switch
Operating Temperature	Operating Temperature: -30°C to +50°C

## Certification and Compliance

