

## Switch Downlight Kit - RW32



### Technical Specifications

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Wattages	3W, 5W, 7W, 9W, 13W, 15W, 18W
Module	X2A, X2A-H, X3A, X3A-H, X15A, X15A-H, X20A
Efficacy	107lm/W, 111lm/W, 121lm/W, 122lm/W, 123lm/W, 124lm/W, 133lm/W, 136lm/W, 140lm/W, 166lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90, CRI: >97
MacAdam Ellipse (SDCM)	SDCM: <3
IP Rating	IP20, IP44, IP54, IP65
Voltage	AC200-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: Lifud, Driver: BOKE, Driver: AIDimming
Size - Diameter	Diameter: 110mmØ
Size - Height	Height: 91mmH, Height: 112mmH, Height: 120mmH, Height: 138mmH
Cut Out Size - Diameter	Cut Out: 100mmØ
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Aluminium & Glass
Operating Temperature	Operating Temperature: -20°C to 45°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Custom Colour
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Custom Colour
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6700K
Mounting Options	Recessed
Lens Options	Honeycomb, Frosted Centre
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 110mmØ
Size - Height	Height: 91mmH, Height: 112mmH, Height: 120mmH, Height: 138mmH
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to 45°C

## Certification and Compliance

