

## Calala Series - 85



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 15W, 17W, 19W, 21W, 23W, 25W, Wattage Selectable: 15W / 20W / 25W
Efficacy	120lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: COB

ATTRIBUTE	VALUES
Driver	Driver: Built In
Size - Diameter	Diameter: 85mmØ
Size - Height	Height: 206mmH
Weight	Weight: 0.8kg
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Aluminium & Transparent Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Gold
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Surface Mounted, TBC
Lifetime	Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 85mmØ
Size - Height	Height: 206mmH
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

