

Calala Series - 100



Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 25W, 27W, 29W, 31W, 33W, 35W, Wattage Selectable: 25W / 30W / 35W
Efficacy	120lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP20
Voltage	AC220-240V
Light Source & Brand	LED: COB

ATTRIBUTE	VALUES
Driver	Driver: Built In
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 220mmH
Weight	Weight: 1.1kg
Beam Angle	Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Aluminium & Transparent Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Gold
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Surface Mounted
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 220mmH
Beam Angle	Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

