

## Taabinga Series - 30W



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	30W
Efficacy	90lm/W
Correlated Colour Index (CRI)	CRI: >80
IP Rating	IP65
IK Rating	IK10
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Driver	Driver: BOKE
Size - Diameter	Diameter: 300mmØ
Size - Height	Height: 85mmH
Weight	Weight: 1.7kg
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -40°C to 60°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Mounting Options	Surface Mounted, Wall Mounted, Ceiling Mounted
Accessories	Microwave Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 300mmØ
Size - Height	Height: 85mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -40°C to 60°C

ATTRIBUTE	VALUES
Accessories	Microwave Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency

## Certification and Compliance

