

Calamia Series - 85



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | TBC, 15W, 20W, 25W, Wattage Selectable: 15W / 20W / 25W |
| Efficacy | 120lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <5, <3 |
| IP Rating | 20, TBC |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Bridgelux COB |
| Driver | Driver: Built In |
| Size - Diameter | Diameter: 85mmØ |
| Size - Height | Height: 270mmH |
| Weight | Weight: 0.96kg |
| Beam Angle | TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Aluminium & Transparent Tempered Glass |
| Operating Temperature | Operating Temperature: -20° to 40° |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black |
| Reflector / Internal Colour | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Gold |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K |
| Mounting Options | Surface Mounted, TBC |
| Lifetime | Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------|--|
| Size - Diameter | Diameter: 85mmØ |
| Size - Height | Height: 270mmH |
| Beam Angle | TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60° |

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20° to 40° |

Certification and Compliance

