

# Jabiru Series

[AES-01-PT03]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 30W, 40W
Efficacy	75lm/W, 110lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	66, TBC
IK Rating	08

ATTRIBUTE	VALUES
Voltage	AC100-277V
Size - Length	Length: 550mmL
Size - Width	Width: 500mmW
Size - Height	Height: 505mmH
Mounting Options	TBC, Post Top
Beam Angle	TBC, Beam Angle: 18°, Beam Angle: 85°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	6kV Surge Protection Device, 10kV Surge Protection Device

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 550mmL
Size - Height	Height: 505mmH
Beam Angle	TBC, Beam Angle: 18°, Beam Angle: 85°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	6kV Surge Protection Device, 10kV Surge Protection Device

## Certification and Compliance

