

Sandon Series



Technical Specifications

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Wattages	5W
Efficacy	30lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <6
IP Rating	IP65
IK Rating	IK08
Voltage	AC220-240V, DC 12V
Light Source & Brand	LED: SMD 2835
Driver	Driver: Built In
Size - Length	Length: 136mmL
Size - Width	Width: 78mmW
Size - Height	Height: 202mmH
Cut Out Size - Length	Cut Out: 130mmL
Cut Out Size - Width	Cut Out: 78mmW
Cut Out Size - Height	Cut Out: 196mmH
Weight	Weight: 0.8kg
Beam Angle	Beam Angle: 70°
Dimming Options	Non-Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Glass Lens
Operating Temperature	Operating Temperature: -20°C to 45°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	Wall Mounted
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 136mmL

ATTRIBUTE	VALUES
Size - Height	Height: 202mmH
Cut Out Size - Length	Cut Out: 130mmL
Cut Out Size - Width	Cut Out: 78mmW
Beam Angle	Beam Angle: 70°
Dimming Options	Non-Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 45°C

Certification and Compliance

