

## Brighton Series - 30-80W



### Technical Specifications

| ATTRIBUTE                     | VALUES             |
|-------------------------------|--------------------|
| Wattages                      | TBC, 30W, 60W, 80W |
| Efficacy                      | 140lm/W            |
| Correlated Colour Index (CRI) | >80, TBC           |
| IP Rating                     | 66, TBC            |
| IK Rating                     | 09                 |
| Voltage                       | AC100-277V         |
| Light Source & Brand          | LED: SMD 3030      |
| Driver                        | Driver: Meanwell   |
| Size - Length                 | Length: 592mmL     |
| Size - Width                  | Width: 255mmW      |
| Size - Height                 | Height: 133mmH     |
| Weight                        | Weight: 5kg        |

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| Mounting Options                    | TBC, Horizontal Pole Arms, Vertical Pole Arms   |
| Beam Angle                          | TBC, Beam Angle: Type II-S - 151° x 81°, Beam Angle: Type II-M - 147° x 72°, Beam Angle: Type III-M - 156° x 71°, Beam Angle: Type IV-M - 100° x 65°, Beam Angle: Type V - 150° |
| Dimming Options                     | Non-Dimmable, TBC, DALI Dimmable  |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K  |
| Accessories                         | Microwave Sensor, PIR Sensor, PhotoElectric Cell, 10kV Surge Protection Device, 20kV Surge Protection Device, Short Circuit Cap   |
| Material of Housing                 | Housing Material: Aluminium   |
| Operating Temperature               | Operating Temperature: -40°C to+50°C  |
| Lifetime                            | Reported L80 @ 85° >72,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes   |

## Product Options

| ATTRIBUTE             | VALUES  |
|-----------------------|---|
| Size - Length         | Length: 592mmL  |
| Size - Height         | Height: 133mmH  |
| Beam Angle            | TBC, Beam Angle: Type II-S - 151° x 81°, Beam Angle: Type II-M - 147° x 72°, Beam Angle: Type III-M - 156° x 71°, Beam Angle: Type IV-M - 100° x 65°, Beam Angle: Type V - 150° |
| Dimming Options       | Non-Dimmable, TBC, DALI Dimmable  |
| Accessories           | Microwave Sensor, PIR Sensor, PhotoElectric Cell, 10kV Surge Protection Device, 20kV Surge Protection Device, Short Circuit Cap   |
| Material of Housing   | Housing Material: Aluminium   |
| Operating Temperature | Operating Temperature: -40°C to+50°C  |

## Certification and Compliance



