

Isla Series - 300



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|---------------|
| Wattages | TBC, 15W |
| Efficacy | 45lm/W |
| Correlated Colour Index (CRI) | >80, TBC |
| IP Rating | 20, TBC |
| Voltage | AC200-240V |
| Light Source & Brand | LED: SMD 2835 |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Size - Diameter | Diameter: 300mmØ |
| Size - Height | 1525mmH |
| Weight | Weight: 1.38kg |
| Beam Angle | TBC, Beam Angle: 125° |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Material of Housing | Iron |
| Material of Optics- Glare control | Optics Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Copper |
| Reflector / Internal Colour | Reflector/Internal: White, Reflector/Internal: Gold, Reflector/Internal: Rose Gold |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K |
| Mounting Options | TBC, Pendant |
| Lamp Life | Lamp Life: L80 B10 @ 4K, CRI80 |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---------------------------------------|
| Size - Diameter | Diameter: 300mmØ |
| Size - Height | 1525mmH |
| Beam Angle | TBC, Beam Angle: 125° |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Material of Housing | Iron |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

