

# Baines Series - 86 - COB Lens

[AES-12-DT860115-CL]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 15W, 20W, 22W, 24W, 26W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	66, TBC
IK Rating	07
Voltage	AC220-240V, 50/60Hz, DC 24V
Light Source & Brand	LED: Cree COB
Driver	Driver: Without Driver, Driver: KGP
Size - Diameter	Diameter: 86mmØ
Size - Width	Width: 136mmW
Size - Height	Height: 150mmH
Weight	Weight: 1-2kg
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum Alloy
Material of Optics- Glare control	Optics Material: Super White Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	TBC, Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Mounting Options	TBC, Wall Mounted
Lens Options	TBC, Honeycomb Louve
Lifetime	Reported L80 @ 85° >63,500 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 86mmØ

ATTRIBUTE	VALUES
Size - Height	Height: 150mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum Alloy
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

