

Switch Downlight Kit - RF13

[AES-10-RF13]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | 3W, 5W, 7W, 9W, 13W, TBC, 15W, 18W |
| Module | X2A, X2A-H, X3A, X3A-H, X15A, X15A-H, X20A |
| Efficacy | 107lm/W, 111lm/W, 121lm/W, 122lm/W, 123lm/W, 124lm/W, 133lm/W, 136lm/W, 140lm/W, 166lm/W |
| Correlated Colour Index (CRI) | >80, >90, >97, TBC |
| MacAdam Ellipse (SDCM) | <3 |
| IP Rating | 20, 44, 54, 65, TBC |
| Voltage | AC200-240V, 50/60Hz |
| Light Source & Brand | LED: Citizen COB |
| Driver | Driver: Lifud, Driver: BOKE, Driver: AIDimming |
| Size - Diameter | Diameter: 100mmØ |
| Size - Height | Height: 78mmH, Height: 103mmH, Height: 111mmH, Height: 129mmH |
| Cut Out Size - Diameter | Cut Out: 90mmØ |
| Weight | Weight: 0.19kg, Weight: 0.275kg, Weight: 0.4kg, Weight: 0.47kg |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 20°, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 38°, Beam Angle: 55°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Aluminium & Glass |
| Operating Temperature | Operating Temperature: -20°C to 45°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Custom Colour |
| Reflector / Internal Colour | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Custom Colour |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6700K |
| Mounting Options | TBC, Recessed |
| Lens Options | Honeycomb, TBC, Frosted Centre |
| Lifetime | Reported L80 @ 55° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 100mmØ |
| Size - Height | Height: 78mmH, Height: 103mmH, Height: 111mmH, Height: 129mmH |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 20°, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 38°, Beam Angle: 55°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to 45°C |

Certification and Compliance

