


Oakbank Series - Round Trimless- 62

[AES-20-C28-RDT-62]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | 3W, 5W, 7W, TBC |
| Efficacy | 100lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <3 |
| IP Rating | 20, TBC |
| Voltage | AC220-240V, 50/60Hz |
| Light Source & Brand | LED: Citizen COB |
| Driver | Driver: BOKE, Driver: AIDimming |
| Size - Diameter | Diameter: 61.6mmØ |
| Size - Height | Height: 79.1mmH |
| Cut Out Size - Diameter | Cut Out: 58mmØ |
| Weight | Weight: 0.48kg |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -15°C to 40°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black |
| Reflector / Internal Colour | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold, Reflector/Internal: Shiny Silver |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K |
| Mounting Options | TBC, Recessed |
| Frame Option | Trimless |
| Lens Options | TBC, Lens |
| Accessories | Honeycomb |
| Lamp Life | Lamp Life: 50,000 hrs with AU plug |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Size - Diameter | Diameter: 61.6mmØ |
| Size - Height | Height: 79.1mmH |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |
| Accessories | Honeycomb |

Certification and Compliance

