


Oakbank Series - Round - 194

[AES-20-C28-RD-194]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 2 x 8W (16W), 2 x 10W (20W), 2 x 12W (24W)
Efficacy	100lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: BOKE, Driver: AIDimming
Size - Diameter	Diameter: 193.8mmØ
Size - Height	Height: 111.7mmH
Cut Out Size - Diameter	Cut Out: 178mmØ
Cut Out Size - Width	Mounting Sleeve: 88mmW
Weight	Weight: 1.06kg
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold, Reflector/Internal: Shiny Silver
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Recessed
Frame Option	Framed
Lens Options	TBC, Lens/Reflector
Accessories	Honeycomb
Lamp Life	Lamp Life: 50,000 hrs with AU plug

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 193.8mmØ
Size - Height	Height: 111.7mmH
Cut Out Size - Width	Mounting Sleeve: 88mmW
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C
Accessories	Honeycomb

Certification and Compliance

