

# Oaks Series - Asymmetrical - 600W



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 600W
Efficacy	152lm/W, 182lm/W
Correlated Colour Index (CRI)	>70, >90, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	66, TBC
IK Rating	08
Voltage	AC200-240V
Light Source & Brand	LED Osram 3737, LED Osram 5050
Driver	Upshine
Size - Length	Length: 655mmL

ATTRIBUTE	VALUES
Size - Width	Width: 266mmW
Size - Height	Height: 257mmH
Weight	15.5kg ± 6%
Tilt	Tilt: 90°
Beam Angle	TBC, F16010 - Symmetrical 11°, F16011 - Symmetrical 15°, F16013 - Asymmetrical Intense 56°, F16014 - Asymmetrical Intense 56°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable - with DALI Programmer, DMX - with DMX Programmer
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Tempered Glass + Polycarbonate Optical Lens
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5700K
Mounting Options	TBC, Pole Mounted, Wall Mounted
Accessories	Visor
Lifetime	Reported L80 @ 85° >90,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 655mmL
Size - Height	Height: 257mmH
Beam Angle	TBC, F16010 - Symmetrical 11°, F16011 - Symmetrical 15°, F16013 - Asymmetrical Intense 56°, F16014 - Asymmetrical Intense 56°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable - with DALI Programmer, DMX - with DMX Programmer
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C
Accessories	Visor

## Certification and Compliance

