

Profile - 1911K

[AES-06-LS1911K]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | 4.8W, 9.6W, 12W, TBC, 16.8W |
| Correlated Colour Temperature (CCT) | CCT: 2300K, CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 6000K |
| Lumens | 112lm/W @ 2300K, 129lm/W @ 2700K, 136lm/W @ 3000K, 139lm/W @ 3500K, 139lm/W @ 4000K, 136lm/W @ 6000K |
| Product Code | C8200-24v-8mm |
| Cutting Unit | 5mm |
| Correlated Colour Index (CRI) | >90 |
| MacAdam Ellipse (SDCM) | <2 |
| Light Source & Brand | LED: SMD |
| IP Rating | 20, 65, 67, TBC |
| Voltage | DC 24V |
| LED's p/m | 200 |
| Size - Width | Width: 19.7mmW |
| Size - Height | Height: 13.1mmH |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver |
| Mounting Options | Surface Mounted, TBC, Recessed |
| Beam Angle | Beam Angle: 110° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Operating Temperature | Operating Temperature: -25°C to 40°C |
| Lifetime | Reported L80 @ 85° >60,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Height | Height: 13.1mmH |
| Beam Angle | Beam Angle: 110° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Operating Temperature | Operating Temperature: -25°C to 40°C |

Certification and Compliance

