

## Switch Downlight Kit - RF15-2



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 2 x 3W (6W), 2 x 5W (10W), 2 x 7W (14W), 2 x 9W (18W), 2 x 13W (26W), 2 x 15W (30W), 2 x 18W (36W)
Module	2 x X2A, 2 x X2A-H, 2 x X3A, 2 x X3A-H, 2 x X15A, 2 x X15A-H, 2 x X20A
Efficacy	107lm/W, 111lm/W, 121lm/W, 122lm/W, 123lm/W, 124lm/W, 133lm/W, 136lm/W, 140lm/W, 166lm/W
Correlated Colour Index (CRI)	>80, >90, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, 44, 54, 65, TBC
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Voltage	AC200-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: Lifud, Driver: BOKE, Driver: AIDimming
Size - Length	Length: 230mmL
Size - Width	Width: 120mmW
Size - Height	Height: 65mmH, Height: 95mmH, Height: 102mmH, Height: 120mmH
Cut Out Size - Length	Cut Out: 210mmL
Cut Out Size - Width	Mounting Sleeve: 100mmW
Weight	Weight: 0.8kg, Weight: 0.55kg, Weight: 0.38kg, Weight: 0.94kg
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 20°, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 38°, Beam Angle: 55°, Beam Angle: 60°
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Aluminium & Glass
Operating Temperature	Operating Temperature: -20°C to 45°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Custom Colour
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Custom Colour
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6700K
Mounting Options	TBC, Recessed
Lens Options	Honeycomb, TBC, Frosted Centre
Lifetime	Reported L80 @ 55° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Size - Length	Length: 230mmL
Size - Height	Height: 65mmH, Height: 95mmH, Height: 102mmH, Height: 120mmH
Cut Out Size - Length	Cut Out: 210mmL
Cut Out Size - Width	Mounting Sleeve: 100mmW
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 20°, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 38°, Beam Angle: 55°, Beam Angle: 60°
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 45°C

## Certification and Compliance

