

# Miller Series - 120-150W

[AES-03-PL01-G7-120-150W]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 120W, 150W
Efficacy	140lm/W, 160lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	66, TBC
IK Rating	09
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: Lumileds
Driver	Driver: SOSEN
Size - Length	Length: 667mmL
Size - Width	Width: 286mmW
Size - Height	Height: 90.5mmH
Weight	Weight: 5.2kg
Tilt	Tilt: 15°
Beam Angle	TBC, Beam Angle: Type II-S - 151° x 81°, Beam Angle: Type II-M - 147° x 72°, Beam Angle: Type III-M - 156° x 71°, Beam Angle: Type IV-M - 100° x 65°, Beam Angle: Type V - 150°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics- Glare control	Optic Material: Tempered Glass
Operating Temperature	Operating Temperature: -40°C to+50°C
Trim / Outer Colour	Trim/Outer: Black, Trim/Outer: Grey, Trim/Outer: Bronze
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	TBC, Pole Mounted
Accessories	20kV Surge Protection Device, Short Circuit Cap, NEMA 3pin Socket, Photocell
Lifetime	Reported L80 @ 85° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 667mmL
Size - Height	Height: 90.5mmH
Beam Angle	TBC, Beam Angle: Type II-S - 151° x 81°, Beam Angle: Type II-M - 147° x 72°, Beam Angle: Type III-M - 156° x 71°, Beam Angle: Type IV-M - 100° x 65°, Beam Angle: Type V - 150°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -40°C to+50°C
Accessories	20kV Surge Protection Device, Short Circuit Cap, NEMA 3pin Socket, Photocell

## Certification and Compliance

