

# Neon Strip - AHT1615



## Technical Specifications

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Metreage	Under 50m
Wattages	10W
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 2700K, CCT: 3000K, CCT: 4000K
Lumens	98lm/W @ 4000K, 94lm/W @ 2700K, 78lm/W @ 2200K, 99lm/W @ 3000K
Cutting Unit	Cutting Unit: 6.25mm
Correlated Colour Index (CRI)	CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5
Light Source & Brand	LED: SMD
IP Rating	IP67
IK Rating	IK08
Voltage	DC 24V
LED's p/m	LEDs/m: 160
Size - Width	Width: 16mmW
Size - Height	Height: 15mmH
Trim / Outer Colour	Trim/Outer: White
Mounting Sleeve - Width	Mounting Sleeve: 17.8mmW
Mounting Options	Surface Mounted, Recessed
Mounting Sleeve - Height	Mounting Sleeve: 7.91mmH
Beam Angle	Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to +50°C
Lifetime	Working Lifetime > 84,000 Hrs

## Product Options

ATTRIBUTE	VALUES
Size - Height	Height: 15mmH
Mounting Sleeve - Width	Mounting Sleeve: 17.8mmW
Mounting Sleeve - Height	Mounting Sleeve: 7.91mmH
Beam Angle	Beam Angle: 110°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to +50°C

## Certification and Compliance

