

Neon Strip - AHS1616

[AES-06-AHS1616]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Metreage | Under 50m |
| Wattages | 10W, TBC |
| Correlated Colour Temperature (CCT) | CCT: 2200K, CCT: 2700K, CCT: 3000K, CCT: 4000K |
| Lumens | 78lm/W @ 3000K, 80lm/W @ 4000K, 61lm/W @ 2200K, 73lm/W @ 2700K |
| Cutting Unit | 6.25mm |
| Correlated Colour Index (CRI) | >90, TBC |
| MacAdam Ellipse (SDCM) | <5 |
| Light Source & Brand | LED: SMD |
| IP Rating | 67, TBC |
| IK Rating | 08 |
| Bend Direction | Side Bend (Horizontal) |
| Voltage | DC 24V |
| LED's p/m | 160 |
| Size - Width | Width: 16mmW |
| Size - Height | Height: 16mmH |
| Mounting Sleeve - Width | Mounting Sleeve: 14.4mmW |
| Mounting Sleeve - Height | Mounting Sleeve: 19.1mmH |
| Trim / Outer Colour | Trim/Outer: White |
| Mounting Options | Surface Mounted, TBC, Recessed |
| Beam Angle | TBC, Beam Angle: 110° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Operating Temperature | Operating Temperature: -20°C to +50°C |
| Lifetime | Working Lifetime > 84,000 Hrs |

Product Options

| ATTRIBUTE | VALUES |
|--------------------------|--------------------------|
| Size - Height | Height: 16mmH |
| Mounting Sleeve - Width | Mounting Sleeve: 14.4mmW |
| Mounting Sleeve - Height | Mounting Sleeve: 19.1mmH |

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Beam Angle | TBC, Beam Angle: 110° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Operating Temperature | Operating Temperature: -20°C to +50°C |

Certification and Compliance

