

# Neon Strip - AHT2020

[AES-06-AHT2020]



## Technical Specifications

ATTRIBUTE	VALUES
Metreage	Under 50m
Wattages	10W, TBC
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 2700K, CCT: 3000K, CCT: 4000K
Lumens	86lm/W @ 2700K, 94lm/W @ 4000K, 72lm/W @ 2200K, 88lm/W @ 3000K
Cutting Unit	6.25mm
Correlated Colour Index (CRI)	>90, TBC
MacAdam Ellipse (SDCM)	<5
Light Source & Brand	LED: SMD
IP Rating	67, TBC
IK Rating	08
Bend Direction	Top Bend (Vertical)
Voltage	DC 24V
LED's p/m	160
Size - Width	Width: 20mmW
Size - Height	Height: 20mmH
Mounting Sleeve - Width	Mounting Sleeve: 22.6mmW
Mounting Sleeve - Height	Mounting Sleeve: 24.7mmH
Trim / Outer Colour	Trim/Outer: White
Mounting Options	Surface Mounted, TBC, Recessed
Beam Angle	TBC, Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to +50°C
Lifetime	Working Lifetime > 84,000 Hrs

## Product Options

ATTRIBUTE	VALUES
Size - Height	Height: 20mmH
Mounting Sleeve - Width	Mounting Sleeve: 22.6mmW
Mounting Sleeve - Height	Mounting Sleeve: 24.7mmH

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to +50°C

## Certification and Compliance

