

# Albany Series - 86

[AES-15-LG-100Y-86]



## Technical Specifications

| ATTRIBUTE | VALUES           |
|-----------|------------------|
| Wattages  | 6W, 8W, 10W, TBC |

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Efficacy                            | 90lm/W   |
| Correlated Colour Index (CRI)       | >90, >95, >97, TBC   |
| IP Rating                           | 65, TBC  |
| Voltage                             | AC220-240V, 50/60Hz  |
| MacAdam Ellipse (SDCM)              | <3   |
| Light Source & Brand                | LED: Bridgelux ECA Series  |
| Driver                              | Driver: Lifud, Driver: AIDimming, Driver: CUPower  |
| Size - Diameter                     | Diameter: 86mmØ  |
| Size - Height                       | Height: 54mmH  |
| Cut Out Size - Diameter             | Cut Out: 75mmØ   |
| Beam Angle                          | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°                                    |
| Weight                              | Weight: 0.5kg  |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable   |
| Material of Housing                 | Housing Material: Aluminium  |
| Material of Optics- Glare control   | Optics Material: Polycarbonate   |
| Operating Temperature               | Operating Temperature: -20°C to 60°C   |
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black   |
| Reflector / Internal Colour         | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K                         |
| Mounting Options                    | TBC, Recessed  |
| Lamp Life                           | Lamp Life: 50,000 hrs  |

## Product Options

| ATTRIBUTE           | VALUES  |
|---------------------|---|
| Size - Diameter     | Diameter: 86mmØ   |
| Size - Height       | Height: 54mmH   |
| Beam Angle          | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable        |
| Material of Housing | Housing Material: Aluminium   |

| ATTRIBUTE             | VALUES                               |
|-----------------------|--------------------------------------|
| Operating Temperature | Operating Temperature: -20°C to 60°C |

## Certification and Compliance

