

Albany Series - 180

[AES-15-LG-100Y-180]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 37W, 39W, 41W, 43W, 45W

ATTRIBUTE	VALUES
Efficacy	90lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	65, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Bridgelux ECA Series
Driver	Driver: Lifud, Driver: AIDimming, Driver: CUPower
Size - Diameter	Diameter: 180mmØ
Size - Height	Height: 109mmH
Cut Out Size - Diameter	Cut Out: 165mmØ
Weight	Weight: 1.5kg
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to 60°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Mounting Options	TBC, Recessed
Lamp Life	Lamp Life: 50,000 hrs

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 180mmØ
Size - Height	Height: 109mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to 60°C

Certification and Compliance

