

Albert Series - 136

[AES-15-LG-200F-136]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 17W, 19W, 21W, 23W, 25W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	65, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Bridgelux ECA Series
Driver	Driver: Lifud, Driver: AIDimming, Driver: CUPower
Size - Length	Length: 136mmL
Size - Width	Width: 136mmW
Size - Height	Height: 83mmH
Cut Out Size - Length	Cut Out: 125mmL
Cut Out Size - Width	Mounting Sleeve: 125mmW
Weight	Weight: 0.75kg
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to 60°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K
Mounting Options	TBC, Recessed
Lamp Life	Lamp Life: 50,000 hrs

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 136mmL

ATTRIBUTE	VALUES
Size - Height	Height: 83mmH
Cut Out Size - Length	Cut Out: 125mmL
Cut Out Size - Width	Mounting Sleeve: 125mmW
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 60°C

Certification and Compliance

