

# Graceville Series - Square - 85



## Technical Specifications

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Wattages                            | 8, 10W, 12W, TBC   |
| Efficacy                            | 90lm/W   |
| Correlated Colour Index (CRI)       | >90, >95, >97, TBC   |
| IP Rating                           | 20, TBC  |
| Voltage                             | AC220-240V, 50/60Hz  |
| Light Source & Brand                | LED: Bridgelux COB   |
| Driver                              | Driver: Lifud, Driver: AIDimming, Driver: CUPower  |
| Size - Length                       | Length: 85mmL  |
| Size - Width                        | Width: 85mmW   |
| Size - Height                       | Height: 89mmH  |
| Cut Out Size - Length               | Cut Out: 75mmL   |
| Cut Out Size - Width                | Mounting Sleeve: 75mmW   |
| Tilt                                | Tilt: 30°  |
| Horizontal Rotation                 | Horizontal Rotation: 355°  |
| Beam Angle                          | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 55°                                    |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable   |
| Material of Housing                 | Housing Material: Die-Casting Aluminum   |
| Operating Temperature               | Operating Temperature: -20°C to +40°C  |
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black   |
| Reflector / Internal Colour         | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K                                     |
| Mounting Options                    | TBC, Recessed  |
| Frame Option                        | Framed   |
| Lamp Life                           | Lamp Life: L80 B10 @ 4K, CRI80   |

## Product Options

| ATTRIBUTE     | VALUES        |
|---------------|---------------|
| Size - Length | Length: 85mmL |

| ATTRIBUTE             | VALUES  |
|-----------------------|---|
| Size - Height         | Height: 89mmH   |
| Cut Out Size - Length | Cut Out: 75mmL  |
| Cut Out Size - Width  | Mounting Sleeve: 75mmW  |
| Beam Angle            | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 55° |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable        |
| Material of Housing   | Housing Material: Die-Casting Aluminum                                  |
| Operating Temperature | Operating Temperature: -20°C to +40°C                                   |

## Certification and Compliance

