


Graceville Series - Square Quad - 158

[AES-15-DHF-SQ-158]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 4 x 8W (32W), 4 x 10W (40W), 4 x 12W (48W)
Efficacy	90lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
IP Rating	20, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Bridgelux COB
Driver	Driver: Lifud, Driver: AIDimming, Driver: CUPower
Size - Length	Length: 158mmL
Size - Width	Width: 158mmW
Size - Height	Height: 90mmH
Cut Out Size - Length	Cut Out: 148mmL
Cut Out Size - Width	Cut Out: 148mmW
Tilt	Tilt: 30°
Horizontal Rotation	Horizontal Rotation: 355°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K
Mounting Options	TBC, Recessed
Frame Option	Framed
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 158mmL

ATTRIBUTE	VALUES
Size - Height	Height: 90mmH
Cut Out Size - Length	Cut Out: 148mmL
Cut Out Size - Width	Cut Out: 148mmW
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

