

Troffer Series - 6060



Technical Specifications

ATTRIBUTE	VALUES
Wattages	32W
Efficacy	115lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <6
IP Rating	IP20
IK Rating	IK06
Voltage	AC220-240V
Light Source & Brand	LED: SMD 2835
Driver	Driver: Built-out
Size - Length	Length: 595mmL
Size - Width	Width: 595mmW
Size - Height	Height: 54mmH
Weight	Weight: 2.37kg
Beam Angle	Beam Angle: 130°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: SPCC
Material of Optics	Optics Material: PMMA + PC
Operating Temperature	Operating Temperature: -10°C to 45°C
Trim / Outer Colour	Trim/Outer: White
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Recessed
Lamp Life	Lamp Life: 50,000 hrs

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 595mmL
Size - Height	Height: 54mmH
Beam Angle	Beam Angle: 130°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable

ATTRIBUTE	VALUES
Material of Housing	Housing Material: SPCC
Operating Temperature	Operating Temperature: -10°C to 45°C

Certification and Compliance

