

# Aura Series 1230



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	18W, 21W, 24W, 27W, 30W, 33W
Efficacy	120lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <4, SDCM: <3
IP Rating	IP40, IP54
IK Rating	IK06
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Driver	VSI Flicker Free
Size - Length	Length: 1195mmL
Size - Width	Width: 295mmW
Size - Height	Height: 25mmH
Weight	Weight: 2.31kg
Beam Angle	Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: PMMA
Corrosion Resistance	Corrosion Resistance: C4
Operating Temperature	Operating Temperature: -30°C to +40°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: Opal
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Surface Mounted, T-Bar Recessed, Plaster Recessed
Lens Options	Frosted PMMA Lens, MicroPrismatic Diffuser
Lifetime	Reported L80 @ 105° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
-----------	--------

03 8761 6734 accounts@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Size - Length	Length: 1195mmL
Size - Height	Height: 25mmH
Beam Angle	Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +40°C

## Certification and Compliance

