

Lameroo Series - 300 Up/Down



Technical Specifications

ATTRIBUTE	VALUES
Wattages	15W, 19W, 21W, 25W
Efficacy	100lm/W
Correlated Colour Index (CRI)	>80
MacAdam Ellipse (SDCM)	<6, <3
IP Rating	40
IK Rating	03
Voltage	AC220-240V
Light Source & Brand	LED: SMD 2835
Driver	Driver: Built In
Size - Diameter	Diameter: 300mmØ
Size - Height	Height: 86mmH
Cut Out Size - Diameter	Cut Out: 215-225mm Ø
Weight	Weight: 2.52kg
Beam Angle	Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polystyrene, Microprismatic Diffuser
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 2CCT: 3000+4000K
Mounting Options	Surface Mounted, Recessed, Pendant
Accessories	Microwave Sensor, Steel Wire Suspension, Pendant Rod Suspension, Wire Harness Suspension
Lifetime	Reported L80 @ 105° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 300mmØ

ATTRIBUTE	VALUES
Size - Height	Height: 86mmH
Beam Angle	Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Microwave Sensor, Steel Wire Suspension, Pendant Rod Suspension, Wire Harness Suspension

Certification and Compliance

