

Neon Strip - AHS1217 - 15W/m

[AES-06-AHS1217-15W]



Technical Specifications

ATTRIBUTE	VALUES
Metreage	Under 50m
Wattages	TBC, 15W
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 2700K, CCT: 3000K, CCT: 4000K
Lumens	69lm/W @ 2700K, 56lm/W @ 2200K, 69lm/W @ 3000K, 67lm/W @ 4000K
Cutting Unit	6.25mm
Correlated Colour Index (CRI)	>90, TBC
MacAdam Ellipse (SDCM)	<5
Light Source & Brand	LED: SMD
IP Rating	67, TBC
IK Rating	08
Bend Direction	Side Bend (Horizontal)
Voltage	DC 24V
LED's p/m	160
Size - Width	Width: 12mmW
Size - Height	Height: 17mmH
Mounting Sleeve - Width	Mounting Sleeve: 14.4mmW
Mounting Sleeve - Height	Mounting Sleeve: 18.9mmH
Trim / Outer Colour	Trim/Outer: White
Mounting Options	Surface Mounted, TBC, Recessed
Beam Angle	TBC, Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to +50°C
Lifetime	Working Lifetime > 84,000 Hrs

Product Options

ATTRIBUTE	VALUES
Size - Height	Height: 17mmH
Mounting Sleeve - Width	Mounting Sleeve: 14.4mmW
Mounting Sleeve - Height	Mounting Sleeve: 18.9mmH

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to +50°C

Certification and Compliance

