

Hall Series 6060

[AES-27-PL-6060-DE]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	11W, 13W, TBC, 16W, 18W, 20W, 22W, 23W, 24W, 26W, 28W, 30W, 32W
Efficacy	90lm/W, 105lm/W
Correlated Colour Index (CRI)	>90, TBC
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: BOKE
Size - Length	Length: 595mmL
Size - Width	Width: 595mmW
Size - Height	Height: 43mmH
Beam Angle	TBC, Beam Angle: 90°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K

ATTRIBUTE	VALUES
Lens Options	TBC, MicroPrismatic Diffuser
Operating Temperature	Operating Temperature: -20°C to 45°C
Accessories	Air Slot

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 595mmL
Size - Height	Height: 43mmH
Beam Angle	TBC, Beam Angle: 90°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -20°C to 45°C
Accessories	Air Slot

Certification and Compliance

