

Fadden Series - Indirect

[AES-01-ST52A]



Technical Specifications

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 40W, Wattage Selectable: 6W / 10W / 15W / 20W
Efficacy	75lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	66, TBC
IK Rating	09
Voltage	AC100-277V
Light Source & Brand	LED: SMD 3030
Driver	Driver: Sosen
Size - Diameter	Diameter: 371mmØ
Size - Height	Height: 420mmH
Weight	Weight: 4.6±0.3kg
Beam Angle	TBC, Beam Angle: R00C52
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate Lens
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	TBC, Post Top, Wall Mounted
Accessories	Microwave Sensor, PhotoElectric Cell, 3pin NEMA Socket, 5pin NEMA Socket, 7pin NEMA Socket
Lifetime	Reported L80 @ 25° >82,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 371mmØ
Size - Height	Height: 420mmH
Beam Angle	TBC, Beam Angle: R00C52

