

Dalara Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, TBC, 15W, 20W, 25W, 30W
Efficacy	98lm/W, 105lm/W
Correlated Colour Index (CRI)	>90, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	20, TBC
Voltage	AC220-240V
Driver	Driver: Built In
Size - Diameter	Diameter: 65mmØ, Diameter: 85mmØ
Size - Height	Height: 248mmH, Height: 278mmH
Weight	Weight: 0.78kg, Weight: 0.88kg
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Aluminium & Transparent Tempered Glass
Operating Temperature	Operating Temperature: -20° to 40°
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Surface Mounted, TBC, Pendant
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 65mmØ, Diameter: 85mmØ
Size - Height	Height: 248mmH, Height: 278mmH
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20° to 40°

Certification and Compliance

