

Kanni Series - 60-100W

[AES-01-ST53-60-100W]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | TBC, 60W, 75W, 100W |
| Efficacy | 160lm/W |
| Correlated Colour Index (CRI) | >70, >80, TBC |
| IP Rating | 66, TBC |
| IK Rating | 09 |
| Voltage | AC220-240V, 50/60Hz |
| Light Source & Brand | LED: SMD 3030 |
| Driver | Driver: Sosen |
| Size - Length | Length: 681mmL |
| Size - Width | Width: 236mmW |
| Size - Height | Height: 128mmH |
| Weight | Weight: 4.5±0.3kg |
| Tilt | Tilt: 15° |
| Beam Angle | TBC, Beam Angle: R01601, Beam Angle: R01602, Beam Angle: R01603, Beam Angle: R01604, Beam Angle: R01605, Beam Angle: R01606, Beam Angle: R01607, Beam Angle: R01609, Beam Angle: R01610, Beam Angle: R01611, Beam Angle: R01613 |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Tempered Glass + Polycarbonate Optical Lens |
| Corrosion Resistance | Corrosion Resistance: C3 |
| Operating Temperature | Operating Temperature: -30°C to +40°C |
| Trim / Outer Colour | Trim/Outer: Grey |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K |

| ATTRIBUTE | VALUES |
|------------------|---|
| Mounting Options | TBC, Post Top, Side Entry, Wall Mounted Adaptor |
| Accessories | Motion Sensor, 3pin NEMA Socket, 5pin NEMA Socket, 7pin NEMA Socket, Photocell |
| Lifetime | Reported L80 @ 25° >82,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Size - Length | Length: 681mmL |
| Size - Height | Height: 128mmH |
| Beam Angle | TBC, Beam Angle: R01601, Beam Angle: R01602, Beam Angle: R01603, Beam Angle: R01604, Beam Angle: R01605, Beam Angle: R01606, Beam Angle: R01607, Beam Angle: R01609, Beam Angle: R01610, Beam Angle: R01611, Beam Angle: R01613 |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -30°C to +40°C |
| Accessories | Motion Sensor, 3pin NEMA Socket, 5pin NEMA Socket, 7pin NEMA Socket, Photocell |

Certification and Compliance

