

Kiama 95 Series - R



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|--------------------|
| Wattages | 20W |
| Efficacy | 95lm/W |
| Correlated Colour Index (CRI) | >90, >95, >97 |
| IP Rating | 20 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Bridgelux COB |
| Driver | Driver: Lifud |
| Shape | Round |
| Size - Diameter | Diameter: 104mmØ |
| Size - Height | Height: 115mmH |
| Cut Out Size - Diameter | Cut Out: 95mmØ |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Charcoal, Trim/Outer: Gold |
| Mounting Options | Recessed |
| Beam Angle | Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 55° |
| Dimming Options | Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 104mmØ |
| Size - Height | Height: 115mmH |
| Beam Angle | Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 55° |
| Dimming Options | Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

