

Polo Series - 80

[AES-27-NL14B]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	8W, TBC
Efficacy	100lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65, TBC
IK Rating	06
Voltage	AC220-240V, 50/60Hz, DC 24V
Light Source & Brand	LED: COB
Size - Diameter	Diameter: 80mmØ
Size - Width	Width: 104mmW
Size - Height	Height: 167mmH

ATTRIBUTE	VALUES
Weight	Weight: 2kg
Vertical Rotation	Vertical Rotation: 180°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 45°, Beam Angle: 50°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics- Glare control	Optics Material: 4mm Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K
Mounting Options	Surface Mounted, TBC, Spike Mounted
Accessories	Cubic Hood, 25° Cubic Hood
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 80mmØ
Size - Height	Height: 167mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 45°, Beam Angle: 50°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Cubic Hood, 25° Cubic Hood

Certification and Compliance

